Ν	o	_	
1 4	v	٠	_

History of corner	establishment since	Original Government Surve	v
riistory or corrier	catating interesting	original dovernment but ve	.7

21602360000

I, Bryan H. Meyer 11地 certify that on the _ of November __19**_83** . I found (evidence) ne evidence) of the Northeast corner of Section 1, T. 15, N, R 2 W Fourth Principal Meridian, and I reestablished said corner according to the Wisconsin Statutes as shown and described hereon.

Dated this 19th day of Dec. 1983.

Deputy County Surveyor

Fred A. Holden was here in February of 1908.

Description of corner evidence found:

Accepted brace post with braces North and East as the best available evidence.



Description of corner and witness monuments, references and accessories used to perpetuate the original or re-established location of this corner:

Crew: Meyer, Perrigo

Date: November 11, 1983 - 12:45 P.M.

Weather: P. Cloudy, Windy, 30°+. Witnesses to corner location:

Bryan H. Meyer

Dennis Perrigo

APPROVED: Harley A. Sime Monroe County Surveyor

SURVEY CONTROL ORDER

Horizontal				
Vertical	_	WISCONSIN COORDINATE SYSTEM		
	East (X)	North (Y)	Elevation (Z)	
Corner].	
Control Sta. Name				

19" Hickory - double blazed, distance is to nail in a hack in the side of the tree.

4.28

Zone

Set Harrison marker, flush.

> Set %"x24" iron 13.6 bar @ end of angle iron fence post with brace.

20.00 Set 3/4"x24" iron bar in fence line.

Set %"x24" iron bar, down 10"+, in hay field.

Section = LOCATION CORNER T_15_N R 2 W

WISCONSIN

of Sheldon City Village of Town _ County of Monroe