established said corner according to the Wisconsin

Statutes as shown and described hereon.

Fourth Principal Meridian, and I re-

19 85 I found

Bryan H. Meyer

(evidence) for evidence of the Section 24

certify that on the \_\_\_\_

Dated this 10th

No.	62
100.	

21602130020

History of corner	establishmen	t since O	riginal (	Government	Survey

Nothing recorded.

Description of corner evidence found:

I accepted the intersection of fences from the East and South as the best available evidence.

in the state of th	WISCONS/N	WARREN TO THE REAL PROPERTY OF THE PARTY OF
Ammin A	Dryan H. Meyer	
	S-1712 2	(0) <b>(5)</b>
M	SURVE NO	& IIII

"Hannath Deputy County Surveyor Description of corner and witness monuments, references and accessories used to perpetuate the original or re-established location of this corner: Crew: Wilhite, Lund Section Date: June 26, 1985 Weather: P. Cloudy, 80°+ N45°W Witnesses to corner location: 22.60 Dallas Wilhite N75°E 19.5 4" Cherry James Lund 12" Maple Bryan H. Meyer Set Harrison, up 2"+. The four bearing trees shown are double blazed; each distance = LOCATION CORNER shown is a slope distance to T\_16\_N R 2 W nail set in a hack in the side of each tree. The bearings WISCONSIN shown are magnetic hand compass SURVEY CONTROL ORDER bearings. Horizontal 6" Maple Vertical WISCONSIN COORDINATE SYSTEM of Ridgeville East (X) Town North (Y) Elevation (Z) Zone Corner Monroe County of \_ Control Sta, Name