

from said 8 Pk 20 Ch. then West 19 Ch. 80 Links. then the distance from the corner of Sec: 17, 18, 19, 20 to the 7 Pk on the West side of Sec: 20 was measured and found to contain 40 Ch 11 Links and the 8 Pk on that Line established at equal distance 1/20 Ch 5 1/2 L of these points from said 8 Pk 20 Ch. 4 Rods Chains was used here also on the E & West Line between Sec 17 & 20 8° 30' and on the N & S Line on Sec: 17 = 8° 25' and on the N & S Line of Sec: 20 9° and on the E & West Line of said Sec: 8° 25'. The gov. corner was adjusted after the field notes; the topography of the ground was carefully taken notice of during the measurement. The Measurements were sworn according to Law. O. R. Dahl

		Remarks
		5 Meanings at 1. N 60° E 282
	6	" " 2 of Oak 10 S 41° W 42 & N Oak 55 S 75° E 85
	3	" " 3. N Oak 13. N 42° W 110
1	2	" " 5 N Oak 10 N 11 1/2° W 18 & W Oak 48 45° W 59
7	8	" " 14 N Oak 4 N 79° E 5 1/2 & W Oak 8 N 35° W 47
		" " 5 N Oak 3 N 60° E 7 & N Oak 6 N 82° E 17
	6	" " 7 N Oak 4 S 9° E 5 & N Oak 3 N 3° W 15
	7	" " 8 N Oak 6 S 45° W 6. no other

I hereby certify that the proceedings are correct, as stated. O. R. Dahl

While remembered that on the 28th day of Nov 1868 I was surveying a alteration of a Highway in Town of Greenfield Monroe Co Wis. by request of the Chairman of the Board of Supervisors Mrs. Gilbert Woodard in presence of him and Supervisor Hall and proceeded as follows to wit Commenced at a point a N Oak 10" in diameter and 2 other N Oaks on the N side close by said tree, with Meanings tree N Oak S 55° W 29. Then said point in the center of the at a former time laid out 40 W and N 52° E and from the 7 Pk on the Line between Sec: 15 & 16, 18, 20. Thence N 1 1/2° W 7 Ch 42 to a Pk 2 Rods West from the Sec. corner thence N 27° W 3 Ch. to a stake thence N 44 1/2° W 1 Ch 63 to a N Oak 4", thence N 55° W 3 Ch 75 to a stake on the S & W Oak 5 N 79° W 89. thence N 12° W 3 Ch 50 to the corner of Sec: 9, 10, 15 & 16. thence on the Sec. Line N 8° W 6 Ch