

...COR. FOUND STK MOLD NEAR FENCE INTERSECTIONS
ALSO ROOTS OF OLD B.T.S. TOOK AFFIDAVIT AND
SET IRON SHAFT. 6" W.O. 575° 30' E 37 FT
4" W.O. 588° E 48.5 FT

COPY OF AFFIDAVIT
STATE OF WISCONSIN }
COUNTY OF MONROE } 55 NOV. 5, 1926
WM SCHINDLER, G.A. SCHINDLER, LOUIS BRUNS
HEREBY MAKE AFFIDAVIT THAT IN THE YEAR
1881 THEY ACCOMPANIED A.B. HOLDEN A SURVEYOR,
WHO SURVEYED SEC 9 T15 NR1W, AND THAT THEY
LOCATED THE N.E. CORNER OF SAID SECTION, AND
DO HEREBY SWEAR THAT THE SAID HOLDEN IN
THEIR PRESENCE OPENED ONE OR MORE OF
THE ORIGINAL WITNESS TREES AT SAID CORNER
AND ESTABLISHED THEREFROM THE SECTION
CORNER AT THE POINT WHERE THE
FENCES ARE NOW ESTABLISHED.

WITNESSES
GAINED WM SCHINDLER
G.A. SCHINDLER
LE BRUNS
CHARLES BOPP
ALFRED TRAMBERT

1/16 COR FORD AXEL
10" W.O. N80° W 0' 2"
10' R.O. 351° E 21.5

1/16 COR REESTABLISHED
SET FORD AXEL
6" W.O. 32° 30' W 73.6 FT
5" HICKORY 37° E 76.0 FT

1/16 COR IRON PIPE
8" R.O. 585° E 150.3 FT
2" PIPE 240° W 91.6 FT

MR. A.J.
BENDSLEY GUYER

1/16 CORNER IRON ROD FORD AXEL
4" R.O. 59° W 10.5 FT
2" HICKORY 112° W 19.4 FT

2" GAS PIPE
2-8" W.O. N 33° W 32"
10" W.O. 580° E

SET HOOKED IRON PIPE
6" BITUM. N39° E 56.6 FT
13" CHERRY N30° E 44.6 FT
10" ELM 64° W 128.0 FT

GEO. BATZEL

1/16 COR REESTABLISHED
LOOKING BOLT & EYE
MILLS SHAFT
2-12" R.O. N18° E 65 FT
12" W.O. 33° E 128.8 FT

HERNANDEZ
1313.5

1/16 SET FORD TIERRO
AND STONE
8" ELM N18° E 37.5 FT
12" ELM N50° W 71.6 FT

CONC. POS
3 1/2" D. W. 102.4 FT
S.W. COR. HOUSE BASEMENT
77.6 FT

1/16 SET IRON ROD
8" W.O. N72° E 20.9 FT
8" R.O. N78° W 39.6 FT

CHARLES

1/16 FORD DEAK SHAFT
8" ELM N85° W 34 FT
10" ELM 581° W 59.6 FT

KINDE

2" IRON PIPE
N82° W 4" W.O. 4.0 FT
12" W.O. 548° E 46.0 FT

1/16 GAS PIPE AND STONE
2-10" W.O. N42° W 92.2 FT
4" W.O. N14° W 87.4 FT

STRATMAN

CHECKED NORTH AND
EAST TO DURGERS AND
WEST TO SEC. COR. DUB AND
FOUND B.T. ROOTS TOOK AFFIDAVIT
AND SET 2" IRON PIPE. ALSO SET
PIPE 240° WEST AND 0° N 210° EAST.
COPY OF AFFIDAVIT

1324.75

1/16 COR
MARKED S. STONE
18" ELM N61° E 132.4'
2-10" ELM N58° W 104.0'

REESTABLISHED
FOUND WHAT WAS
APPARENTLY STK.
MOLD. ALL OTHER
EVIDENCE DONE
SET IRON ROD
18" ELM 528° E 29.0 FT
2-12" MARLES N106° E 64.5

1/16 COR
SET MICHEL FOOT RAIL
8" ASH 557° E 97.8 FT
6" ASH N78° W 105.0 FT

STATE OF WISCONSIN }
COUNTY OF MONROE }
H.M. SHERBURN,
DATA, 3/15/25; T15
WISCONSIN; T15
THAT ON OR ABOUT
AND HILARUE
SAID SECTION
CERTAIN ELM,
AS 17" W.O.

STATE OF WISCONSIN }
COUNTY OF MONROE } 55 NOV. 5, 1926
WM SCHINDLER, G.A. SCHINDLER, MYRON DOTEN
DO HEREBY SWEAR THAT THEY REMEMBER THE
OLD W.O. WITNESS TREE DESCRIBED IN THE GOVERNMENT
SURVEY NOTES AS "W.O. 18" 575° E 61" FOR THE SW. COR. OF
SEC 9 T15 NR1W, AND THAT THE ROOTS UNCOVERED BY THE
SURVEY PARTY UNDER FRANK J. DAVIS ARE UNDOUBTLY THE
ROOTS OF THE SAME TREE AND ARE IN THE SAME POSITION
AS THE OLD TREE AND THAT THE CORNER ESTABLISHED
HEREFROM IS CORRECT.
WITNESSES

I HEREBY CERTIFY THAT THE

COR. REESTABLISHED
 SET FORD AXEL
 6" W.D. 3" 30W 73.6 FT
 5" HIGHOR 137E 76 OF
 COR. IRON PIPE
 8" ROD 3.85E 150.3 FT
 1" PIPE 3.85W 71.2 FT

MR. A.J.
 BENDLEY GUYER

FOUND IRON PIN SET BY HOLDEN
 AT INTERSECTION OF OLD FENCES
 WHICH TESTIMONY SHOWED HAD
 BEEN IN THE SAME LOCATION FOR 30
 YEARS AND HAD BEEN PLACED
 WHEN THE ORIGINAL CORNER AND
 B.T.'S HAD BEEN STANDING. ALSO
 CHECKED TO CREEKS SHOWN IN
 ORIGINAL NOTES. SET SANDSTONE
 ALONGSIDE IRON PIN. 4" ELM N89°W 121.3 FT
 4" W.D. N27°W 113 FT.

SET MARKED IRON PIPE FORD AXEL
 6" B. AND 133E 56 FT SW COR. OF RAIL 75 OF
 13" CHARR 133E 44.1 FT 10" ELM 347W 128.2 FT

GEO. BATZEL

SET FORD AXEL AND STONE
 JUST EAST OF IT.
 B.T. 16" ELM. 52°W 111.4 FT
 8" W.D. NORTH 211.5 FT

CONC. POST
 2" DIA. 130.4 FT
 SW COR. OF BENDLEY
 178.6 FT

CHARLES

COR. FOUND HOLDEN'S STR.
 AND B.T. ACCEPTED CORNER
 SET FORD AXEL
 8" B. OAK N11°30'E 59.5' FT
 8" " 55.5'E 38.5 FT

1/4" COR. PIPE AND STONE
 2-10" W.D. N48°W 92.2 FT
 4" W.D. N14°W 87.4 FT

STRATMAN

1/4" IRON ROD
 B.T. ON ROCKFACE 34°W 30 FT
 4" B.O. N 25°W 20 FT

REESTABLISHED
 FOUND WHAT WAS
 APPARENTLY STR.
 HOLD ALL OTHER
 EVIDENCE DONE
 SET IRON ROD
 18" ELM 50SE 25.0 FT
 2-12" MARLES N10E 64.5

S.E. COR. FENCE COR CHECKS WITH ORIGINAL
 NOTES ON DISTANCES TO CREEK. AFFIDAVITS.
 ACCERTED EVIDENCE AND SET IRON AXEL
 5 12" ELM 54.3E 13.10 FT.
 14" BURROAK N79°W 92.7 FT
 AFFIDAVIT COPY.

STATE OF WISCONSIN)
 COUNTY OF MONROE) ss. CHAS STRATMAN, MYRON DOTEN,
 H.M. SHERBURN, EACH FOR HIMSELF BEING DULY SWORN, ON
 OATH, SAYS: THAT HE IS A RESIDENT OF THE STATE OF
 WISCONSIN; THAT HE IS FAMILIAR WITH SECTION 10, T15N R1W;
 THAT ON OR ABOUT 1902 HE ACCOMPANIED ONE BERT ABBOTT
 AND H. LARUE SURVEYORS, WHO LOCATED THE S.E. COR. OF
 SAID SECTION 10, THAT THEY USED AS A REFERENCE
 CERTAIN ELM, WHICH IS DESCRIBED IN THE ORIGINAL NOTES
 AS "12" W.D. 34°W 75". THAT THE ORIGINAL GOVERNMENT
 MARKS WERE UNCOVERED ON SAID TREE IN THEIR PRESENCE
 BY BERT ABBOTT AND LARUE; THAT THE CORNER SO
 ESTABLISHED HAS BEEN AND STILL IS ACCEPTED AS SAID
 SECTION CORNER
 SUBSCRIBED AND SWORN
 TO BEFORE ME THIS
 2ND DAY OF NOV 1926
 A.H. SMITH
 COURT COMMISSIONER
 MONROE COUNTY, WIS.

I HEREBY CERTIFY THAT THE
 ABOVE SKETCH IS A CORRECT
 REPRESENTATION OF SECTION
 R1W AS SURVEYED BY ME IN
 NOV 1926.
 Frank Dwyer
 ENGINEER

CHAS STRATMAN
 MYRON DOTEN
 H.M. SHERBURN