	79	
Vo.	1 2	

'eddersen, do hereby Hi	ory of corner establishment since Original Government Survey
-------------------------	--

41501232000

Dated this 23 day of DEC. 1982.

Registered Land Surveyor

Fred Holden was here in November of 1906.

Description of corner evidence found:

Accepted fence corner as best available evidence.

M NO.	Description of corner and witness mo			tuate the original or re-e	¦ ⊬nai	il/wash	ner in blaze		Section	24
FORM			asher in				ed orange		1	
ŭ.		blaze	,	downed	( ) in	9" bur	roak / )			
YOR	Witnesses to corner location:		d orange red oak	fence—		nce wir or oak	re through hail/washer in			i   
É	Lawrence Feddersen	211 13	200 00n O C	30.90'	יוט ד	38	blaze and painted			
É					α <u>΄</u>		orange in 10" map	اما		
S	Thomas Mangene	MINIMITALITY.					ordinge in it maps	<u> </u>		
×ΤΝ	suring!	5CONS MILLIN	set Harrison 1	Monument-	F	dowr	ned fence	Ψ		
000	The state of the s	LAWRENCE A. FEDDERSEN S-1226 TOMAH WIS. VD SURVERNING			a a		asher in blaze .nted orange in d oak	o T_15	= LOCATIO	N CORNER
		America	ved: Harle	va. sing	ļ				WISCON	SIN
	SURVEY CONTROL ORDER				Ţ					
	Horizontal	NON	ROE CO. S	BULTVEYOR						
	Vertical		WISCONSIN COORDINATE SYSTEM							
	East (	X} No	orth (Y)	Elevation (Z)	Zone	X	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	}		
	Corner						County of Monroe			
	Control Sta. Name									